

Boat Manufactured By:

Xpress

THE ORIGINAL ALL-WELDED BOAT

199 Extrusion Place • Hot Springs, AR

(501) 262-5300

www.xpressboats.com

XPRESS X23 BAY

Length	23' 0"
Beam	8' 6"
Dry Weight (Boat Mfr. Pub)	2,296 lbs
Maximum HP	250 hp
Fuel Capacity	75 gal
Weight as Tested	3,594 lbs

VF250XA

Horsepower	250 hp
Induction	EFI/VCT/DOHC
Displacement	4.2L
Weight (Estimated)	555 lbs
Gear Ratio	1.75:1

ENGINE MOUNTING HEIGHT

Mounting Hole Position	#3
------------------------	----

PROPELLER(S)

Series	Saltwater Series II™
Diameter x Pitch	15 x 20
Yamaha Part #	6CE-45932-20-00
Propeller Material	Polished Stainless Steel

TEST CONDITIONS

Number of People	2
Air / Water Temperature (Fahrenheit)	80° F / 78° F
Elevation (in feet above sea level)	312'
Wind Velocity	5-10 MPH

COMMENTS

Test weight includes 50 gallons of fuel, 1 battery, 24V trolling motor, 10" hydraulic jack plate, safety and test equipment.

YPB#: PB_XPR_X23BAY_VF250XA_07-30-18_ALM



Engine: Yamaha VF250XA

Boat: Xpress X23 Bay

Configuration: Single

Test Date: 29-Jul-2018



PERFORMANCE DATA

RPM	MPH	GPH	MPG
1000	5.1	1.2	4.25
1500	7.4	2.3	3.22
2000	11.4	3.6	3.17
2500	21.8	4.7	4.64
3000	28.5	6.2	4.60
3500	33.3	8.5	3.94
4000	38.2	11.9	3.22
4500	44.1	15.3	2.89
5000	48.8	19.0	2.57
5500	54.1	21.8	2.48
6000	58.6	23.6	2.48
0-30 MPH: 4.20 seconds			

NOTICE TO CONSUMER

The information and data contained in this Performance Bulletin is approximate and subject to many different factors and variables. It is provided as a guideline only and should not be relied upon as representative of actual performance. Your boat's performance may be different than the information contained in this Performance Bulletin due to various factors, including your boat's actual weight, wind and water conditions, temperature, humidity, elevation, bottom paint, boat options affecting wind/water drag and/or boat weight, and operator ability. Please confirm the specifications and performance data on your specific boat/engine combination with your dealer prior to purchase. Please also keep in mind that the data contained in this Performance Bulletin may or may not have been performed using Yamaha PowerMatched components. Yamaha reserves the right to change the specifications and performance data of this Performance Bulletin or engine without notice. This document contains many of Yamaha's valuable trademarks. It may also contain trademarks belonging to other companies. Any references to other companies or their products are for identification purposes only, and are not intended to be an endorsement.