



PERFORMANCE BULLETIN

Engine: Yamaha VF225LA

Boat: Xpress® H20®

Configuration: Single

Test Date: 19-Apr-2011




PERFORMANCE DATA

RPM	MPH	GPH	MPG
1000	5.9	1.4	4.21
1500	7.7	2.7	2.85
2000	10.9	3.6	3.03
2500	27.8	4.9	5.67
3000	33.9	6.6	4.4
3500	40	9.1	4.4
4000	46.6	11.9	3.92
4500	53.6	14.8	3.62
5000	61.3	17	3.61
5500	68.6	19.8	3.47
5900	74.6	20.2	3.69

Seconds to Plane: 2.9

Seconds 0-30 MPH: 4.7



NOTICE TO CONSUMER

The information and data contained in this Performance Bulletin is approximate and subject to many different factors and variables. It is provided as a guideline only and should not be relied upon as representative of actual performance. Your boat's performance may be different than the information contained in this Performance Bulletin due to various factors, including your boat's actual weight, wind and water conditions, temperature, humidity, elevation, bottom paint, boat options affecting wind/water drag and/or boat weight, and operator ability. Please confirm the specifications and performance data on your specific boat/engine combination with your dealer prior to purchase. Please also keep in mind that the data contained in this Performance Bulletin may or may not have been performed using Yamaha PowerMatched components. Yamaha reserves the right to change the specifications and performance data of this Performance Bulletin or engine without notice. This document contains many of Yamaha's valuable trademarks. It may also contain trademarks belonging to other companies. Any references to other companies or their products are for identification purposes only, and are not intended to be an endorsement.

XPRESS® H20®

Length	20' 0"
Beam	8' 0"
Dry Weight (Boat Mfr. Pub)	1,166 lbs
Maximum HP	225 hp
Fuel Capacity	30 gal
Weight as Tested	2,446 lbs

VF225LA

Horsepower	225 hp
Displacement	4.2 L
Weight (Estimated)	505 lbs
Gear Ratio	1.75

ENGINE MOUNTING HEIGHT

Mounting Hole Position	#2
Anti-Ventilation Plate Height	5 3/4" Above Bottom

PROPELLER(S)

Series	VMAX® Ventless Series
Diameter x Pitch	15 1/8 x 25
Yamaha Part #	6CB-45972-00-00
Propeller Material	Polished Stainless Steel

TEST CONDITIONS

Number of People	2
Air / Water Temperature (Fahrenheit)	80° F / 64° F
Elevation (in feet above sea level)	301'
Wind Velocity	10-15 MPH

COMMENTS

Test weight includes 3/4 tank of fuel, 3 batteries, bow-mounted trolling motor, 8" jack plate, safety and test equipment. Fuel consumption data gathered with Yamaha Command Link® fuel management system. Zero-to-30 speed data gathered with aftermarket speedometer. Other speed data gathered with GPS receiver.

YPB#: PB_XPR_H20_VF225LA_2011-04-19_ALM

Boat Manufactured By:

Xpress
199 Extrusion Place • Hot Springs, AR
(501) 262-5300

www.xpressboats.com (<http://www.xpressboats.com>)

