

Boat Manufactured By:

Xpress

THE ORIGINAL ALL-WELDED BOAT

199 Extrusion Place • Hot Springs, AR

(501) 262-5300

www.xpressboats.com

XPRESS H18

Length	17' 10"
Beam	7' 9"
Dry Weight (Boat Mfr. Pub)	1,215 lbs
Maximum HP	115 hp
Fuel Capacity	18 gal
Weight as Tested	2,360 lbs

VF115LA

Horsepower	115 hp
Induction	EFI
Displacement	1.8L
Weight (Estimated)	377 lbs
Gear Ratio	2.15:1

ENGINE MOUNTING HEIGHT

Mounting Hole Position	#3
Ventilation Plate Height	2-3/4" Above Boat Bottom

PROPELLER(S)

Series	Talon SS
Diameter x Pitch	13-1/8 x 20
Yamaha Part #	6N7-45978-00-00
Propeller Material	Polished Stainless Steel

TEST CONDITIONS

Number of People	2
Air / Water Temperature (Fahrenheit)	95° F / 80° F
Elevation (in feet above sea level)	344'
Wind Velocity	5-10 MPH

COMMENTS

Test weight includes 18 gallons of fuel, 3 batteries, 24 volt trolling motor, battery charger, 6" manual jackplate, safety and test equipment.

YPB#: PB_XPR_H18_VF115LA_08-03-20_ALM



Engine: Yamaha VF115LA

Boat: Xpress H18

Configuration: Single

Test Date: 2-Aug-2020



PERFORMANCE DATA

RPM	MPH	GPH	MPG
1000	3.8	0.6	5.91
1500	5.8	1.1	5.43
2000	7.3	1.8	4.10
2500	12.6	2.6	4.85
3000	21.8	3.1	7.11
3500	27.5	4.1	6.68
4000	32.8	5.4	6.05
4500	37.5	6.5	5.81
5000	41.5	9.2	4.53
5500	45.8	10.9	4.19
6000	49.8	12.2	4.07
6300	50.0	12.0	4.16
0-20 MPH: 6.63 seconds			

NOTICE TO CONSUMER

The information and data contained in this Performance Bulletin is approximate and subject to many different factors and variables. It is provided as a guideline only and should not be relied upon as representative of actual performance. Your boat's performance may be different than the information contained in this Performance Bulletin due to various factors, including your boat's actual weight, wind and water conditions, temperature, humidity, elevation, bottom paint, boat options affecting wind/water drag and/or boat weight, and operator ability. Please confirm the specifications and performance data on your specific boat/engine combination with your dealer prior to purchase. Please also keep in mind that the data contained in this Performance Bulletin may or may not have been performed using Yamaha PowerMatched components. Yamaha reserves the right to change the specifications and performance data of this Performance Bulletin or engine without notice. This document contains many of Yamaha's valuable trademarks. It may also contain trademarks belonging to other companies. Any references to other companies or their products are for identification purposes only, and are not intended to be an endorsement.